




Technical Data Sheet

Terrace Oil

Decking Oil Natural

Cod. 4971XX-IL



DESCRIPTION

TERRACE OIL is a blend of natural oils and resins, special for the finishing of outdoor wooden floors, perfect for exotic timbers and surfaces nearby swimming pools, not cracking nor peeling. Thanks to its high wetting properties, high solid content and low viscosity, it's ideal to nourish, protect and decorate or restore terraces, providing resistance to water, weathering and foot traffic. The special pigmented versions grant a natural and uniform color-effect. Extremely easy application and maintenance (wide open time even in difficult climate conditions, no sanding required). Enriched with UV filters and additives against wood harmful agents, it's the ideal solution for

any outdoor wooden surface.

APPLICATION FIELDS

Outdoor untreated wooden floors or previously treated with oils from the same range. Wooden terraces, piers, poolsides; garden furniture, outdoor wooden surfaces in general.

CERTIFICATIONS AND COMPLIANCE

Compliance EN71.III Safe for toys for children

YIELD

16-20 m²/l per layer depending on the method of application and wood absorption rate.

Characteristics	U.M.	Value
Density	g/cm ³	0,87 ± 0,02
Viscosity Ford#4	sec.	17 ± 2
Dry residual	%	55 ± 5
Single coat drying time (20°C)	hours	6 ± 2
Complete drying time (20 ° C)	hours	24 ± 6



METHOD OF USAGE



Clean the surface to be treated by grease, silicones, old varnishes or traces of dirt; if possible, lightly sand.



Spread the product homogeneously with a brush, roller or rag, avoiding excesses.



Allow to dry for 6-8 hours.



Sanding is not normally required. If necessary, proceed with sanding with 180-220 grit sandpaper.



Apply at least a second coat.



Wait 24 hours for complete drying.

TECHNICAL RECOMMENDATIONS

The choice of a colored version ensures that the finish is considerably more resistant to ultraviolet rays than the transparent version of the same product.

In the case of saline water pools, it is strongly advisable to protect the surface with 1-2 coats of Deckin Oil HD.

Mix well before use.

To obtain a regular drying, apply uniform and not excessive thicknesses.

Oils are not compatible with different types of basecoats: it is therefore recommended to apply them on raw wood or on finishes previously obtained with oils from the same line. It is advisable not to apply under direct

sun, on hot surfaces, in the presence of strong wind, rain, fog or with danger of night frosts.

Always perform a preliminary test on a sacrificial area to see if the effect matches the desired one.

The use on hard and / or exotic woods may result in a considerable lengthening of the drying times.

Always ensure adequate ventilation during and after application to facilitate the oxidation process and therefore allow a correct hardening of the applied oil layer.

Oils are subject to a physiological yellowing, both inside the container and once applied: it is a natural phenomenon related to the origin of the raw material.

CLEANING AND DILUTION

Solvoil 06 o Solvoil Plus.

COMPLEMENTARY PRODUCTS AND APPLICATION TECHNOLOGIES

Please find below our recommendations for regular or extraordinary maintenance:

1- **Naturaqua Exterior Wood Cleaner** cod. 0075 for deep cleaning

2- **Naturaqua Extra Strong Wood Cleaner** cod. 0091 for the complete removal of any oil trace.

3- **Naturaqua Deck soap** cod. 0026 - for regular cleaning (daily use).

4- **Decking Oil HD** cod. 4971 – for a particularly decorative effect or for saline water pools.

PACKAGE

Cod. 4971-IL	6 x 1Lt
Cod. 4977-IL	2 x 2,5Lt
Cod. 4972-IL	2 x 5Lt
Cod. 4975-IL	1 x 10Lt
Cod. 4973-IL	1 x 20Lt



AVAILABLE COLORS

Available colors: 50 white, 174 Natural Iroko, 512 Oak, 729 Larch, 173 Teak, 302 Cherry, 622 Mahogany, 582 Rosewood, 1472 Wenge, 632 Dark Walnut, 1462 Green Pine, 1012 Grey, 601 Black ebony.

BORMA COLOR SYSTEM



Compatibile pastes:
Oil pigments of CO series.

STORAGE

Store in a cool and well-ventilated place; keep the container closed when not in use. Keep away from heat, open flames, sparks and other sources of ignition.

The product has a storage time of 24 months from the date of production.

WARNINGS

Read the SDS before use.

Wood sawdust, cotton cloths, paper and similar products soaked in liquid product, and left in such conditions, may cause self-ignition.

Therefore, in the case of such cleaning materials or anything else, be careful to favor good ventilation to allow rapid drying of the product or to wet it with water before disposal. Observe the safety regulations in force.

Product for professional use.

The data shown in this data sheet are typical average values obtained based on commonly accepted test methods. These data, as well as the properties of any sample supplied do not imply any legal guarantee or insurance

obligation. We recommend the user to evaluate the suitability of our products in particular uses or specific applications.



Exterior Line
OIL TECH.



BORMA WACHS®
Wood Professional Cosmetics

Product code: **4971XX-IL**
Revision: **05 del 04.03.2019**